

BABY LOCK SEWING ACCESSORIES

Open Toe Foot

(BLQ2-OT)

Instructions




The open width makes it perfect for projects that require visibility and stability, such as appliqué, surface embellishments, and stitching around intricate areas with decorative stitches.

INSTRUCTIONS:


Removing the presser foot

Raise the presser foot (a).



Attaching the presser foot

Lower the presser foot holder (b) until the notch (c) is directly above the pin (d). Lower the presser foot holder (b) and the presser foot (e) will engage automatically.



The Precision Dual-Feed Quilting System (PDQ) feeds the fabric from the top and bottom simultaneously to ensure matching of the fabric layers, used for quilting layers of fabric and batting, and when matching checked, striped or plaid fabrics.

To Activate and Deactivate the Precision Dual-Feed Quilting System (PDQ)



To activate the PDQ system, raise the presser foot. Lower the PDQ mechanism slowly and swing the PDQ mechanism forward under the back of the presser foot until it is engaged and stays in the system. To deactivate the PDQ system, raise the presser foot, pull down on the mechanism and swing it to the rear then raise the PDQ up.



FOR THE LOVE OF SEWING

1. Remove the presser foot.
2. Attach the Open Toe Foot and engage PDQ.
3. Select desired stitch.
4. Place the fabric under the foot and sew.
5. The Open Toe Foot is the perfect foot for attaching appliqués or stitching around intricate areas of decorative stitches. You will notice that this foot has a larger groove cut out of the underside to accommodate thicker stitches and decorative threads.



FOR THE LOVE OF SEWING

800-422-2952

www.babylock.com